Flexbar Diffuser Track

Slimline linear luminaires

This is a track-mounted version of the elegant Flexbar Diffuser linear luminaire, suitable for a range of adaptable lighting installations.

The dropped diffuser, available in opal and low-glare, provides a side glow, creating a softer appearance while supporting illumination on the walls and ceiling, and aiding compliance with EN 12464-1 and LG7.

For use with the Track system.

Applications: offices, meeting rooms, circulation, education, leisure, and retail.

- Track mounted individual luminaires
- TM66 score of 2.6 - LIA/CIBSE certification scheme TSD-012 verified
- White (RAL 9016) or black (RAL 9005) body finishes
- Polycarbonate TP(a) fire-retardant diffuser in opal or low glare options
- Low glare optics for EN12464-1 / LG7 (<3000cd/m² @ 65°) when using the low glare diffuser



IP20 | **Up to 129.4 LL/CW** | **LUXGUARD** | **TM66 circularity score 2.6**

Specification

Mounting	**Track**	IP rating	**IP20**
Nominal size	**840 mm** **1400 mm**		

Sustainability

TM66 circularity score	**2.6**

Lighting

Optic	**Low glare diffuser** **Opal diffuser**	Lumen output	**1,065 lm - 4,400 lm**
Efficacy	**Up to 129.4 LL/CW**		

Flexbar Diffuser Track

Power

LED power	**8 W - 30 W**	Circuit power	**10 W - 34 W**

Construction

Finish	**Full polyester powder coat**	Body colour	**Black (RAL 9005)** **White (RAL 9016)**
Optical assembly	**Polycarbonate TP(a) fire-retardant diffuser**		


LED characteristics

CRI	**80+**	Colour temperature	**4000 K**
Rated life (hours)	**100 K - L90/B10**	LED protection	**LUX Guard**
Driver efficiency	**>77%**	Replaceable light source	**Yes**
Power factor	**>0.9**	MacAdam ellipse	**3 Step**
Flicker metric	**IEC TR 61547-1: PstLM ≤1.0 / SVM ≤0.4**		

Compliance

UKCA	**Yes**	CE	**Yes**
Energy efficiency class	**This product contains a light source of energy efficiency class B**	Thermoplastic rating	**TP(a)**

Dimensions



Flexbar Diffuser Track

Range



Product	LED power	Nominal size	Optic	Lighting control system
FDT Flexbar Diffuser Track	**08** 8 W **12** 12 W **19** 19 W	**S** 840 mm	**O** Opal diffuser **L** Low glare diffuser	**A** Dimming (DALI) **L** Non-dimming
	12 12 W **21** 21 W **30** 30 W	**M** 1400 mm		

Black version - suffix catalogue number with **B6**

E.g. **FDT08SOAB6** = 8 W / 840 mm / Opal diffuser / Dimming (DALI) / Black version

Flexbar Diffuser Track



Click or scan here

View Flexbar Diffuser Track variants using our online filtering tool



Information is correct as of 04 Nov 2026, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.